



2018 COB Reflector General Introduction

- * Interchangeable for various light beams with consistent measurements.
- * Better light performance and higher LOR
- * Applicable for multi-brands COB items
- * Anodise with highly pure aluminum for long lasting performance
- * Never yellowing and cracking on the surface unlike low ended plastic reflectors

Tel: (+852) 2465 5679 Fax: (+852) 2455 8434
 E-mail: info@widegarm.com.hk
 http://www.widegarm.com.hk
 www.facebook.com/Widegarm
 Hong Kong Office: Flat A, 3/F., Tak Wing Ind. Building, 3 Tsun Wen Rd.,
 Tuen Mun, N.T., Hong Kong
 China Factory: Fulusha Village, Shatian Town, Dongguan City,
 Guangdong Province, China

OD 50mm

 1028 Beam Angle: 26° Lamp Hole: ø12.5, ø14, ø15.5, ø16.7, ø18, ø22	 1128 Beam Angle: 36° Lamp Hole: ø12.5, ø14, ø15.5, ø16.7, ø18, ø22	 1021 Beam Angle: 45° Lamp Hole: ø6, ø12.5, ø14, ø15.5, ø16.7, ø18, ø22, ø23	 1010 Beam Angle: 29° Lamp Hole: ø13.5, ø18, ø20.5, ø22	 1009 Beam Angle: 18° Lamp Hole: ø13.5, ø18, ø20.5, ø22	 1017 Beam Angle: 18° Lamp Hole: ø13.5, ø17
---	---	--	---	---	---

OD 72mm Classic

 2201 Beam Angle: 11° Lamp Hole: ø10, ø12.5, ø13.5, ø14, ø18, ø20, ø23, ø25	 2207 Beam Angle: 24° Lamp Hole: ø12.5, ø20, ø21, ø23, ø25	 2202 Beam Angle: 28° Lamp Hole: ø10, ø12.5, ø13.5, ø14, ø18, ø20, ø25, ø30
---	--	---

OD 72mm Zhaga

 2094 Beam Angle: 15° Lamp Hole: ø13.5, ø18, ø20, ø22.5	 2095 Beam Angle: 23° Lamp Hole: ø13.5, ø18, ø20, ø23	 2096 Beam Angle: 55° Lamp Hole: ø13.5, ø18, ø20, ø23
---	---	---

Locking Structure
TE-2 Spring

WG-STTE

OD 82mm

 3150 Beam Angle: 14° Lamp Hole: ø13.5, ø15.5, ø18, ø20	 3204 Beam Angle: 24° Lamp Hole: ø12.5, ø14, ø18, ø20, ø23, ø25	 3205 Beam Angle: 31° Lamp Hole: ø10, ø12.5, ø14, ø18, ø20, ø23, ø25	 3206 Beam Angle: 16° Lamp Hole: ø18, ø20, ø23, ø25	 3207 Beam Angle: 34° Lamp Hole: ø18, ø20, ø23, ø25
---	---	--	---	---

WG SPOS

Osram Prevaled Core, Lumens
 VS Panasonic Luga, Bridgelux Vero
 Fortimo SLM, Sharp Intermo
 Connectors: WG, TE-1

WG SPPH

Philips Fortimo SLM

WG SPXM

Xicato XTM/XIM

WG DCXC

Xicato XSM

WG STTB-SS02 WG STTB-SH03 WG STTB-S503 WG STTB-EH04

BJB
 AAG
 Tridonic SLE

OD 91.5mm

 3158 Beam Angle: 15° Lamp Hole: ø13.5, ø22.5	 3163 Beam Angle: 22° Lamp Hole: ø13.5	 3159 Beam Angle: 34° Lamp Hole: ø13.5, ø20, ø25
---	--	--

OD 94mm

 3167 Beam Angle: 20° Lamp Hole: ø23	 3168 Beam Angle: 32° Lamp Hole: ø23
--	--

*above items' OD could be reduced to be 91.5mm

OD 111mm

 4219 Beam Angle: 18° Lamp Hole: ø20, ø23	 4220 Beam Angle: 35° Lamp Hole: ø20, ø23	 4221 Beam Angle: 40° Lamp Hole: ø20, ø23	 4201 Beam Angle: 11° Lamp Hole: ø14, ø23, ø25, ø28.5, ø30, ø35	 4301 Beam Angle: 27° Lamp Hole: ø10, ø14, ø23, ø25, ø28.5, ø30, ø35	 4401 Beam Angle: 39° Lamp Hole: ø14, ø23, ø25, ø28.5, ø29.5, ø30, ø35
---	---	---	---	--	--

 4134 Beam Angle: 25° Lamp Hole: ø18, ø20, ø23, ø25, ø30	 4133 Beam Angle: 32° Lamp Hole: ø18, ø20, ø21, ø23, ø25
--	--

OD 121mm

 4185 Beam Angle: 13° Lamp Hole: ø23	 5142 Beam Angle: 35° Lamp Hole: ø14, ø23, ø25
--	--

OD 160mm

 6995 Beam Angle: 94° Lamp Hole: ø10.5, ø15.8, ø16	 6135 Beam Angle: 43° Lamp Hole: ø23, ø25, ø36.5
--	--

For Cube / DLM

 6995 Beam Angle: 99° Lamp Hole: ø65, ø68	 6510 Beam Angle: 90° Lamp Hole: ø65, ø68	 7053 Beam Angle: 100° Lamp Hole: ø65, ø68	 6304 Beam Angle: 48° Lamp Hole: ø65, ø68	 4173 Beam Angle: 77° Lamp Hole: ø65, ø68	 5057 Beam Angle: 66° Lamp Hole: ø65, ø68
---	---	--	---	---	---

Luminus Tunable White/ Warm Dimming Connectors

Connector No.: WC-CTMB (Tunable White) WC-CDM6-9 (Warm Dim)

Tunable White OCT 1800K-4000K / CCT 2700K-6500K

Warm Dimming COBs 3000K to 1800K / 4000K to 2700K

Connectors

BJB AAG STUGGH Molex WG-Citizen DW-Sharp GW6NGW JCS0C WG-Cree CXA1304/1507 CXA1816/3050 WG-Basic Core 800/1500/2000/3000/5000lm TE-1 TE-2

