



# 2016 New Reflector Spec. Sheet



- ★ Inter-changeable for various light beams with constant measurements.
- ★ Wider shoulder for Zhaga modules and connectors
- ★ Better light performance and higher LOR

## 3167

Beam Angle: **22°**  
Dimension: OD94x50

|                  |                            |                        |                 |                |
|------------------|----------------------------|------------------------|-----------------|----------------|
| For WG Connector | For WG Connector with Lock | For BJB/AAG Connectors | For Fortimo SLM | For Xicato XTM |
|------------------|----------------------------|------------------------|-----------------|----------------|

**Spring:**

Zhaga Lock

SLM Lock

XTM Lock

Ø23

50

Ø85

Ø94

**Intensity(unit:cd)**  
Xicato XTM 1200lm    θav(½):22°

## 3168

Beam Angle: **32°**  
Dimension: OD94x50

|                  |                            |                        |                 |                |
|------------------|----------------------------|------------------------|-----------------|----------------|
| For WG Connector | For WG Connector with Lock | For BJB/AAG Connectors | For Fortimo SLM | For Xicato XTM |
|------------------|----------------------------|------------------------|-----------------|----------------|

**Spring:**

Zhaga Lock

SLM Lock

XTM Lock

Ø23

50

Ø85

Ø94

**Intensity(unit:cd)**  
Xicato XTM 1200lm    θav(½):32°

