

LED Heat Sink

Xicato Series



Twist Locker



Adaptor Ring

Remark: () is rating required by Xicato

Part Number	Picture	Description	Thermal Class	Weight(g)	Dissipation area (mm ²)	LED Module	Driver Current (mA)	Measurments
SK-C49A		Ø49x35mm	C(B)	74g	25423mm ²	XSM 400lm CRI≥80	700mA	
		Ø49x45mm	D	99g	32458mm ²	XSM 700lm CRI≥80	1050mA	
SK-C70C		Ø70x40mm	F(E)	148g	61572mm ²	XSM 1000lm CRI≥80	1050mA	
		Ø70x70mm	G(F)	254g	106790mm ²	XSM 1300lm CRI≥80	1050mA	
SK-C85B		Ø85x30mm		286g	34266mm ²	XSM 700lm CRI≥80	1050mA	
		Ø85x60mm		572g	65080mm ²	XSM 1300lm CRI≥80	1050mA	
SK-C99.5A		Ø99.5x20mm	E	132g	37246mm ²	XSM 1000lm CRI≥80	1050mA	
		Ø99.5x25mm	F	165g	45947mm ²	XSM 1300lm CRI≥80	1050mA	
		Ø99.5x40mm	K	264g	72053mm ²	XSM 2000lm CRI≥80	1050mA	
		Ø99.5x70mm	N(Q)	445g	124264mm ²	XSM 3000lm CRI≥80	1050mA	
SK-C135A		Ø135x40mm	P(K)	525g	109787mm ²	XSM 2000lm CRI≥80	1050mA	
		Ø135x55mm	Q	742g	149093mm ²	XSM 3000lm CRI≥80	1050mA	
SK-C165C		Ø165x30mm		708g	109697mm ²	XSM 2000lm CRI≥80	1050mA	
		Ø165x45mm		1062g	160198mm ²	XSM 3000lm CRI≥80	1050mA	
SK-S9447A		160x94x47mm		598g	243298mm ²	XLM 3000lm CRI≥80	1050mA	
AR49		Ø49.5x8.5mm		10g		Adaptor Ring / For XSM		