






General Recessed Lighting

Hong Kong Lighting Fair 2017 Booth No.1C-D40
Lighting & Building, Frankfurt, 2018 Hall 10.1

<p>1300LM IP54</p>  <p>68mm ø84</p> <p>LD3304</p>	<p>1300LM</p>  <p>80mm ø88</p> <p>LD220</p>	<p>3000LM</p>  <p>130mm ø146</p> <p>LD6511</p>	<p>3000LM IP54</p>  <p>130mm ø146</p> <p>LD6521</p>	<p>3000LM</p>  <p>165mm ø190</p> <p>LD6068</p>
<p>1300LM</p>  <p>58mm ø65</p> <p>LD230</p>	<p>1300LM</p>  <p>85mm ø90</p> <p>LD401</p>	<p>2000LM</p>  <p>198mm ø205</p> <p>LD8027</p>	<p>1800LM</p>  <p>118mm ø138</p> <p>LD3018</p>	<p>2000LM</p>  <p>142mm ø155</p> <p>LD4019</p>
<p>3000LM</p>  <p>175mm ø194</p> <p>LD6511-C0B</p>	<p>2000LM</p>  <p>175mm ø194</p> <p>LD6115-CUBE</p>	<p>3000LM</p>  <p>212mm ø227</p> <p>LD8115-CUBE</p>	<p>3000LM IP65</p>  <p>212mm ø245</p> <p>LD8112</p>	<p>4000LM</p>  <p>200mm ø220</p> <p>LD10028</p>
<p>1300LM IP54</p>  <p>77x77mm 87x87</p> <p>LD3404</p>	<p>1300LM</p>  <p>77x77mm 87x87</p> <p>LD3409</p>	<p>2000LM</p>  <p>125x125mm 140x140</p> <p>LD4033</p>	<p>3000LM</p>  <p>153x153mm 170x170</p> <p>LD6033</p>	<p>5000LM</p>  <p>184x184mm 200x200</p> <p>LD8044</p>
<p>1800LM</p>  <p>158mm ø180</p> <p>LD7027</p>	<p>1300LMx2 IP54</p>  <p>77x77mm 388x110</p> <p>LD030</p>	<p>反射罩 87x87 IP54</p>  <p>HA404</p>		<p>反射罩 87x87 IP54</p>  <p>HA406</p>

For more details about our products, please visit homepage:
www.widegerm.com.hk



Widegerm Lighting Ltd.
 Hong Kong Office: Flat A, 3/F., Tak Wing Ind. Building, 3 Tsun Wen Rd., Tuen Mun, N.T., Hong Kong
 China Factory: Fulusha Village, Shatian Town, Dongguan City, Guangdong Province, China

匯湛照明有限公司

Surface Mounted Square Down Light

800/1300 lumen
 Item No.: LD407-8W
 LD407-13W
 LED Power: 8W/800lm
 13W/1300lm

Beam Angles: 11° 24° 32°

Light Sources: Lens Glass Triplex Glass

Colour Temp.: 3000K 4000K
 CRI (Ra) : Ra80 Ra90 Ra95
(Please contact the sales department for other special requirements.)

Driver: Dimmable Flicker Over

Special Light Sources: 10W 15W

Warm Dimming: With Custom dimmer, user automatically tones the colour temperature from 3000K down to as low as 1800K (version B from 4000K to 2700K) as the LED is dimmed.
 Tunable White: With two-channel driver, tunable white module can be driven the two colours independently, allowing smooth tuning from warm white 2700K to cool white 6500K (version B will be from 3000K to 4000K) by varying their relative drive current.

Colour Selection: White Black Silver Grey
(Gold or other special surface treatment requirements, please contact the sales department.)

Remark:

- Different Colour Temperature and Color Rendering Index (CRI) to be your options
- Different brands and models of drivers and LED light source for your selections
- Prices are different depend on your final configurations.
- Special discount would be offered if order is larger or for special partners.
- Shipping cost to be confirmed as Ex-work basis
- For more options, please contact our sales department. All information provided is for reference only. Widegerm reserves the right to change subject to our final version.
- 3 year warranty under main components' vendor conditions. We only replace products or components one by one, no extra cost to supplier.